



> PRINT

ECOSYS P2035d

B/W DESKTOP PRINTER
FOR A4 FORMAT

MADE TO BE
YOUR **DEPENDABLE**
PARTNER.



A reliable and robust office solution for perfect b/w printing day in, day out! The ECOSYS P2035d desktop printer is very compact and its standard duplex printing functionality helps you reduce your paper consumption. It has long-life components that reduce downtime and large paper cassettes holding up to 550 sheets. It will carry out daily office tasks without hassle or noise. This printer is a perfect companion for busy days: discreet, hardworking and reliable!

- > Up to 35 pages per minute in A4
- > Standard duplex functionality for double-sided printing
- > Max. paper capacity of up to 550 sheets
- > PowerPC 405F5 / 360 MHz, up to 544 MB RAM
- > Compact design, robust and dependable
- > Highly reliable thanks to long-life components
- > Exceptionally low printing costs



ECOSYS stands for ECOlogy, ECONomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

KYOCERA NetViewer

KYOCERA NetViewer enables the complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunctionals from any Windows® PC and thus gives you the means to streamline your network administration. It also supports standardised SNMP.

ECOSYS P2035d

GENERAL

Technology: KYOCERA ECOSYS Laser

Engine speed: Up to 35 pages per minute in A4

Resolution: Fast 1,200 dpi

Duty cycle: Max. 20,000 pages per month
Max. average 2,000 pages per month

Warm-up time: Approx. 15 seconds or less from power on

Time to first page: Approx. 6 seconds or less

Dimensions (W x D x H): 375 mm x 393 mm x 250 mm

Weight: Approx. 12 kg (main unit)

Power source: 220 / 240 V, 50 / 60 Hz

Power consumption

Printing: 535 W

Ready mode: 7.1 W

Sleep mode: 2.6 W

Noise (ISO 7779 / ISO 9296)

Printing in full-speed mode: 53.3 dB(A) LpA

Printing in half-speed mode: 49.6 dB(A) LpA

Ready mode: 30.7 dB(A) LpA

Safety standards: GS, TÜV, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray; 60 – 220 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 – 215.9 x 356 mm), Folio, Oficio 2; 250-sheet universal paper cassette, 60 – 120 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm – 215.9 x 297 mm), Folio, Oficio 2; Max. input capacity incl. options: 550 sheets A4

Duplex functionality: Duplex as standard supports A4, Folio, Oficio 2, Letter, Legal, 60 – 105 g/m²

Output capacity: 250 sheets face-down

PRESCRIBE IIe

With the KYOCERA page design and control language PRESCRIBE IIe, even complex graphics, logos and forms (multipart forms) can be created independently on the system, and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

STATUS MONITOR AND COMMAND CENTRE

The status monitor shows the current printer's condition and gives direct access to the command centre for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

CONTROLLER

CPU: PowerPC 405F5 / 360 MHz

Memory: 32 MB RAM + EComemory + 512 MB in 1 SDRAM DIMM slot

Standard interface: USB 2.0 (Hi-Speed), KUIO interface slot

Controller language: PRESCRIBE IIe

Emulations: PCL6 / PCL5e incl. PjL, KPDL 3 (PostScript 3 compatible) with automatic emulation switching (AES), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630

Operating systems: All current Windows operating systems, Mac OS X Version 10.5 or higher

Fonts / Barcodes: 80 outline fonts accessible in all emulations, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode PDF-417

CONSUMABLES

TK-160 Toner-Kit: Microfine toner for 2,500 pages A4 in accordance with ISO/IEC 19752

Capacity of starter toner is 1,000 pages A4 in accordance with ISO/IEC 19752

OPTIONS

PF-100 Paper feeder (max. 1 unit): Max. 250 sheets; 60 – 120 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm – 215.9 x 297 mm)

CB-130 Cabinet: Desk with storage capacity

Memory upgrade: 1 SDRAM DIMM slot (128, 256, 512 MB)

CompactFlash card: 1 slot (up to 4 GB) for printing forms, fonts, logos, macro storage

Optional interfaces

PS159: Wireless LAN (802.11b/g)

PS1109 Gigabit Ethernet: 10BaseT / 100BaseTX / 1000BaseT (RJ-45)

PS129 Fibre Optic: 100BaseSX (SC)

PS1129 Gigabit Fibre Optic: 1000BaseSX (SC)

MODEL VARIATIONS

ECOSYS P2035dn: Incl. integrated IB-23 Network card

MAINTENANCE

MK-180 Maintenance-kit: 100,000 pages

WARRANTY

1-year warranty* as standard. KYOCERA guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYO LIFE Up to 3-year on-site warranty extensions available for printer and options.

